


DATASHEET

Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 30m



General data

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801. Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper (patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class, Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

Features of EFB fiber optic patch cables

Tension relief reinforced with aramid yarn

Halogen-free and flame-retardant sheath according to IEC-60754-2, IEC-60332-1 and IEC-61034

EFB fiber optic connectors meet the minimum quality class Grade B/2 according to IEC-61753-1 for singlemode and Grade A/1 for multimode according to IEC 61753-122-2 (UPC cut)

100% tested and with individual measurement report

Allgemeine Daten

APC version	False
Number of fibres	2
Jacket Material	LSZH

General data

Colour outer sheath	orange
Bend optimized fiber	OM2 acc. to IEC60793-2-10 type A1a.1

This datasheet was created automatically on 20-05-2024 . Technical changes reserved.



DATASHEET

Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 30m

Connector colour 2	beige
Halogen free	acc. IEC60754-1
Cable type	I-V(ZN) H
Anti-kink sleeve	put-on
Category	OM2
Connector colour 1	beige

Mechanical characteristics

Min. Bending radius (Dynamic)	20xOD
Max. Tension	160 N
Min. Bending radius (Static)	10xOD
Cable Ø	2.0 mm

Cable construction

Cable Construction	Duplex
--------------------	--------

Kabelaufbau

Fibre type	Multi mode 50/125
Type of connector connection 2	SC duplex
Type of connector connection 1	LC-Duplex

Cable sheath

Flame retardant	According to EN 50265-2-1
Halogen free (according to EN 50267-2-3)	True
Low smoke	acc. IEC61034-1

Umgebungsbedingungen

Storage Temperature	-20 - 85 °C
Operating Temperature	-20 - 75 °C

Übertragungstechnische Eigenschaften

Quality class Multimode	A/1 according to IEC-61753-222-2
-------------------------	----------------------------------

Normen, Zulassungen, Zertifizierungen

Cable Conform to Standard	IEC 60793-2
---------------------------	-------------

This datasheet was created automatically on 20-05-2024 . Technical changes reserved.




DATASHEET

Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 30m

Available variants

ArtNr.	Bezeichnung	Length	Längentoleranz
O0320.0,50	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 0.5m	0.5 m	±5 %
O0320.1	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 1m	1.0 m	±5 %
O0320.2	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 2m	2.0 m	±5 %
O0320.3	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 3m	3.0 m	±5 %
O0320.5	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 5m	5.0 m	±5 %
O0320.7,5	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 7.5m	7.5 m	±5 %
O0320.10	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 10m	10.0 m	±5 %
O0320.15	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 15m	15.0 m	±5 %
O0320.20	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 20m	20.0 m	±5 %
O0320.25	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 25m	25.0 m	±5 %
O0320.30	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 30m	30.0 m	±5 %
O0320.35	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 35m	35.0 m	±5 %
O0320.40	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 40m	40.0 m	±5 %
O0320.45	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 45m	45.0 m	±5 %
O0320.50	Duplex Jumper LC-SC 50/125μ, OM2, LSZH, orange, 2.0mm, 50m	50.0 m	±5 %

Drawings



This datasheet was created automatically on 20-05-2024 . Technical changes reserved.